

**BEAM-STEERING OF MULTI-CHROMATIC LIGHT  
USING ACOUSTO-OPTICAL DEFLECTORS AND  
DISPERSION-COMPENSATORY OPTICS**

**CROSS-REFERENCE TO RELATED APPLICATIONS**

The present application claims the benefit under 35 U.S.C. § 119(e) of U.S. Provisional Patent Application Serial No. 60/256,221, filed December 15, 2000, the disclosure of which is incorporated herein by reference.

**BACKGROUND OF THE INVENTION**

The present invention relates generally to optical instrumentation and relates more particularly to the beam-steering of light using acousto-optical deflectors.

Optical instruments have long played an important role in the study of physical and biological phenomena. Light microscopes, in particular, have been used for more than one hundred years to gain insight into the structure of biological media. As can readily be appreciated, achieving high spatial resolution remains one of the foremost objectives of a light microscope. This objective, however, is often hampered by the fact that biological media, by their very nature, are typically highly scattering with respect to light. Consequently, objects located beneath the surface of a biological medium are often difficult to observe with high resolution using light microscopy. As a result, a number of different approaches have been undertaken in an effort to counteract the light scattering effects of biological media.

One such approach is the confocal microscope, an example of which is disclosed in U.S. Patent No. 4,863,226, inventors Houpt et al., which issued September 5, 1989, and which is incorporated herein by reference. In a confocal microscope, light is brought to focus on or within a sample, and the light emitted from the illuminated sample is then brought to focus on a pinhole

positioned in front of a detector, the pinhole being used to prevent light scattered by the sample from reaching the detector. Often in a confocal microscope, the illuminating light is laser light, and a galvanometer or the like is placed along the optical path of the illuminating laser light to create a scanning beam of illuminating laser light. Laser scanning confocal microscopes are often used to create fluorescence images of a sample, with the illuminating laser light being used to excite native and/or extrinsic fluorophores present within the sample, and the non-scattered component of the fluorescent light emitted from said fluorophores being passed through the pinhole and detected by the detector.

One of the problems associated with the use of laser scanning confocal microscopes in fluorescence imaging is that the detected light signal is typically weak. This is because, of all the fluorescence photons generated by the sample, only the non-scattered (i.e., ballistic) photons generated at the illuminating focus (i.e., on-focus) are permitted to pass through the pinhole and are detected by the detector. In other words, not only are the undesirable fluorescence photons generated at loci other than the illuminating focus (i.e., off-focus) excluded from detection but so are the desirable scattered on-focus fluorescence photons, said scattered on-focus fluorescence photons representing a significant portion of the on-focus fluorescence photons.

Another problem associated with the use of laser scanning confocal microscopes in fluorescence imaging is that the intensity of the illuminating light necessary to generate an appreciable detected signal often has the undesirable consequence of adversely affecting the fluorophore (i.e., photobleaching) or adversely affecting the sample through a fluorophore-mediated event (i.e., photodamage). Moreover, because the illuminating light must travel through the sample

to the illuminating focus, the above-mentioned effects of photobleaching and photodamage are not confined to the illuminating focus.

One form of laser scanning microscopy that has been devised to address the types of shortcomings discussed above in connection with laser scanning confocal fluorescence microscopy is multi-photon excited fluorescence laser scanning microscopy. In multi-photon excited fluorescence laser scanning microscopy, excitation of a fluorophore is achieved by the simultaneous absorption by the fluorophore of two or more photons of low energy that combine their energies to provide the requisite energy for transition of the fluorophore to its excited state. For example, two photons of lower energy red or infrared light may be used to excite a fluorophore typically excitable by one photon of higher energy ultraviolet light. Because multi-photon absorption requires two or more photons for each excitation, its rate depends on the square of the instantaneous intensity and is, therefore, almost completely confined spatially to the high-intensity region at the focal point of the strongly focused excitation laser.

Consequently, because the requisite energy for excitation is spatially confined to the focal point of the illuminating laser, multi-photon excited fluorescence laser scanning microscopy does not result in off-focus photobleaching or photodamage and does not require the placement of a pinhole in front of the detector, as in confocal fluorescence microscopy, to reject off-focus fluorescence photons. Because such a pinhole is unnecessary in multi-photon excited fluorescence laser scanning microscopy, both scattered and ballistic on-focus fluorescence photons are detected, thereby yielding a stronger signal than if only ballistic on-focus fluorescence photons were detected. Furthermore, because longer wavelength photons typically scatter less in biological media than do shorter wavelength photons, one can achieve improved depth penetration of the media using multi-



As a second-order reaction in the concentration of incident photons, second-harmonic generation laser scanning microscopy possesses the same intrinsic resolving power as two-photon excited fluorescence laser scanning microscopy. In addition, second-harmonic generation laser scanning microscopy, like multi-photon excited fluorescence laser scanning microscopy and unlike laser scanning confocal fluorescence microscopy, does not require the placement of a pinhole in front of the detector. However, unlike multi-photon excited fluorescence laser scanning microscopy, multi-harmonic generation laser scanning microscopy does not require that the object being imaged possess a fluorescent molecule. Instead, multi-harmonic generation laser scanning microscopy merely requires that the object possess the appropriate nonlinear susceptibility. Moreover, as contrasted with multi-photon excited fluorescence laser scanning microscopy, multi-harmonic generation laser scanning microscopy does not involve the absorption and re-emission of energy as only scattering occurs therein and it occurs instantly. Yet another difference between multi-photon excited fluorescence laser scanning microscopy and multi-harmonic generation laser scanning microscopy is that the latter technique requires the use of forward-scattered detection and collection optics since harmonic light propagates only in the forward direction with respect to the exciting light whereas the former technique does not require such forward placement as it relies upon fluorescent light, which is radiated isotropically.

Additional information relating to multi-harmonic generation laser scanning microscopy is provided in the following published documents, both of which are incorporated herein by reference: Campagnola et al., "High-Resolution Nonlinear Optical Imaging of Live Cells by Second Harmonic Generation," Biophysical Journal, 77:3341-9 (December 1999); and Moreaux et al., "Coherent Scattering in Multi-Harmonic Light Microscopy," Biophysical Journal, 80(3):1568-74 (March 2001).

Acousto-optical deflectors are devices commonly used in the high-speed scanning of light beams. An acousto-optical deflector typically comprises a solid transparent block of homogenous material (e.g.,  $\text{TeO}_2$ ) onto which one or more rf transducers are bonded. The transducers produce acoustic plane waves that travel through the block of homogeneous material and, thereby, cause a periodic refractive index modulation within the block. Due to the large difference in the respective velocities of sound and light, incident light “sees” this refractive index modulation as a stationary grating and is deflected at a specific angle (the so-called “Bragg angle”) with respect to the acoustic wave. As seen by the following equation, the deflection of the incident beam is proportional to the frequency of the acoustic wave (and, thus, the period of the refractive index modulation):

$$\theta = 2 \cdot \theta_{\text{Bragg}} = 2 \cdot \frac{\lambda f}{2v} = \frac{\lambda f}{v} \quad [\text{Eq. 1}]$$

where  $\theta$  = deflection angle with respect to the incident beam [radians],  $\lambda$  = wavelength of light,  $f$  = acoustic wave frequency, and  $v$  = velocity of the acoustic wave.

A linear scan of an incident beam by an acousto-optical deflector of the type described above can be produced by ramping the frequency of the rf signal that drives the transducers. Other patterns of beam deflection by an acousto-optical deflector, such as movement of the beam through a set of predefined positions, without an intervening sweep (the so-called “random access” steering), are also possible by applying appropriate command functions to the transducers.

Because acousto-optical deflectors function without moving parts, imaging systems that use acousto-optical deflectors to generate scanning beams possess certain advantages over imaging systems that use movable deflection mirrors to generate scanning beams. More specifically, imaging systems that use acousto-optical deflectors can acquire images at rates from about 30 to nearly 500

Hz and are anticipated to operate at even higher (kHz) repetition rates in random access mode. By contrast, if control of the deflection mirrors involves feedback with a linear command function, the line scan frequency of the deflection mirrors is typically less than 500 Hz. This results in a maximal image acquisition rate of about 1 Hz, a serious limitation to real-time analysis. Higher scan frequencies can be attained when the mirrors are made to be freely oscillating without feedback, but then the mirror deflections become essentially sinusoidal, instead of linear. This has the drawback that only a fraction of the working cycle of a full deflection period (the fraction in which the sine function is approximately linear) is available for data acquisition or that significant post-acquisition processing is required to linearize the image. In addition, the inert mass of a scanning deflection mirror precludes the abrupt accelerations and decelerations that would be required for random access.

Because acousto-optical deflectors of the type described above permit laser scanning at high repetition rates, it would seem to be desirable to utilize such acousto-optical deflectors for laser scanning in multi-photon laser scanning microscopy. However, this has not been feasible because the ultrashort laser pulses that are needed for multi-photon excitation (and for multi-harmonic generation) at biologically tolerable average power levels are not typically monochromatic, but rather, span spectral ranges of up to tens of nanometers. As a result, because the incident ultrashort light pulses on an acousto-optical deflector are typically multi-chromatic, the acousto-optical deflector acts essentially as a diffraction grating for the incident ultrashort light pulses, laterally separating their spectral components (see Fig. 1A). Consequently, pulses with a center wavelength of 900 nm and a bandwidth of about 20 nm, as is typical for the 100 fs pulses used in multi-photon laser scanning microscopy (and in multi-harmonic generation laser scanning microscopy), are

dispersed by 0.0729 degrees using an acousto-optical deflector having an acoustic velocity of 4322 m/s and a frequency range centered at 275 MHz. This corresponds to a normalized dispersion of 0.00365 deg/nm. Since a linear scan spans a range of acoustic frequencies, the normalized dispersion usually varies slightly across the scan area, as shown in TABLE I.

TABLE I

Frequency	Dispersion	Dispersion with correction of -0.00365 [deg/nm]
MHz	deg/nm	deg/nm
225	0.00299	-0.00066
275	0.00365	0
325	0.00431	+0.00066

In view of the above, it can readily be appreciated that the lateral dispersion of ultrashort laser pulses by an acousto-optical deflector blurs the focus of the exciting beam in the scan direction, with the following two adverse consequences for multi-photon laser scanning microscopy: (i) the spatial resolution in the scan direction is severely compromised; and (ii) the multi-photon excitation efficiency (and the multi-harmonic generation efficiency) is lowered.



## **SUMMARY OF THE INVENTION**

It is an object of the present invention to provide a technique for ameliorating the above-described problem of spectral dispersion of multi-chromatic ultrashort light pulses by acousto-optical deflectors.

Such a technique is provided, in accordance with the teachings of the present invention, by positioning a spectrally dispersive element, such as a prism, along the path of the multi-chromatic ultrashort light pulses in such a way that said dispersive element disperses the multi-chromatic ultrashort light pulses in a direction opposite to the spectral dispersion caused by the acousto-optical deflector. Preferably, the opposing dispersion provided by the spectrally dispersive element equals that provided by the acousto-optical deflector for at least a portion of the dispersed light.

According to one aspect of the invention, there is provided an apparatus for steering a beam of light, said apparatus comprising (a) an acousto-optical deflector; and (b) a spectrally dispersive element, said spectrally dispersive element and said acousto-optical deflector being optically coupled to one another. The spectrally dispersive element may be positioned either in front of said acousto-optical deflector or behind said acousto-optical deflector, said spectrally dispersive element preferably being oriented relative to said acousto-optical deflector so that said spectrally dispersive element disperses multi-chromatic light in a direction opposite to that dispersed by said acousto-optical deflector, said spectrally dispersive element also preferably being constructed to disperse multi-chromatic light in an amount equally opposite to, for at least a portion of said multi-chromatic light, that dispersed by said acousto-optical deflector.

The spectrally dispersive element is preferably a prism but may alternatively be a grating or a second acousto-optical deflector. The apparatus may further comprise one or more mirrors for use

in directing the beam along a particular path. More specifically, where the spectrally dispersive element is positioned in front of said acousto-optical deflector, said apparatus preferably further comprises a rotatable mirror and a fixed mirror, said rotatable mirror and said fixed mirror being positioned between spectrally dispersive element and said acousto-optical deflector and serving to redirect the beam, after it passes through the spectrally dispersive element, to the entrance axis of the acousto-optical deflector. The rotatable mirror imparts adjustability for wavelength-dependent variations in the deflection of light by the spectrally dispersive element.

A second set of acousto-optical deflector and spectrally dispersive element can be used, for example, to steer the beam along a second axis perpendicular to the first axis.

The above-described beam steering apparatus can be used to scan a plurality of contiguous locations or can be used to randomly deflect the beam within a plurality of possible locations.

According to another aspect of the invention, there is provided a method of steering a beam of light, said method comprising the steps of (a) providing a beam of light; (b) passing said beam of light through a spectrally dispersive element; and (c) deflecting said beam of light using an acousto-optical deflector. Preferably, the spectrally dispersive element is oriented to disperse multi-chromatic light in a direction opposite to that dispersed by said acousto-optical deflector, and said spectrally dispersive element is preferably constructed to disperse multi-chromatic light, for at least a portion of said multi-chromatic light, in an amount equal to that dispersed by said acousto-optical deflector. The light may be passed through the spectrally dispersive element either before or after being deflected by the acousto-optical deflector.

The beam of light steered by the present method may be either a continuous beam of light or a pulsed beam of light. Preferably, the beam of light is a beam of ultrashort laser light pulses

having a pulse duration of less than one picosecond and a bandwidth of no more than about 40 nm. Said light preferably has a wavelength in the range of about 400 to 1000 nm.

The present invention is also directed to an apparatus for spectrally dispersing multi-chromatic light traveling along a first axis, said apparatus comprising (a) a spectrally dispersive element, disposed along said first axis, for dispersing said multi-chromatic light; (b) a pair of mirrors optically coupled to said spectrally dispersive element and positioned thereafter to redirect said dispersed light along said first axis. Preferably, one of said pair of mirrors is a rotatable mirror to adjust for wavelength-dependent variations in the deflection of said dispersed light, and the other of said pair of mirrors is a fixed mirror.

The aforementioned apparatus preferably further comprises means for rotating said rotatable mirror, said rotating means comprising a rotatably mounted arm and a motor for rotating said rotatably mounted arm, said rotatable mirror being fixedly mounted on said rotatably mounted arm. Preferably, said motor is controllable by computer. Said apparatus preferably further comprises a base, said spectrally dispersive element, said pair of mirrors, said rotatably mounted arm and said motor being mounted on said base.

The present invention is additionally directed to a method of imaging a sample using multi-photon excited fluorescence laser scanning microscopy, said method comprising the steps of (a) providing a sample containing fluorescent molecules which radiate photons of a first characteristic energy; (b) producing a scanning beam of ultrashort laser light pulses, said scanning beam being produced by (i) providing a beam of ultrashort laser light pulses comprising photons of a second characteristic energy, wherein said second characteristic energy is less than said first characteristic energy and wherein the simultaneous absorption of a plurality of said photons of said second

characteristic energy by said fluorescent molecules causes the fluorescence of said fluorescent molecules, (ii) passing said beam through a spectrally dispersive element, and (iii) deflecting said beam using an acousto-optical deflector, (iv) wherein said spectrally dispersive element is oriented to disperse multi-chromatic light in a direction opposite to that dispersed by said acousto-optical deflector; (c) focusing said scanning beam at a focal point within said sample to produce an illumination intensity sufficiently high only at said focal point to produce molecular excitation and fluorescence of said sample by simultaneous absorption of a plurality of incident photons; (d) detecting the fluorescence produced by said sample; and (e) using the detected fluorescence to form an image of the sample.

Preferably, the spectrally dispersive element used in the aforementioned method is constructed to disperse multi-chromatic light, for at least a portion of said multi-chromatic light, in an amount equal to that dispersed by said acousto-optical deflector. The scanning beam producing step described above preferably further comprises scanning the sample in a direction perpendicular to said first axis, said scanning in a direction perpendicular to said first axis comprising the use of a scanning mirror or a second acousto-optical deflector and a second spectrally dispersive element, said second spectrally dispersive element being oriented relative to said second acousto-optical deflector so as to disperse multi-chromatic light in a direction opposite to that dispersed by said second acousto-optical deflector.

The present invention is further directed to a multi-photon excited fluorescence laser scanning microscope for forming a magnified image of a sample, said sample containing fluorescent molecules which radiate photons of a first characteristic energy, said multi-photon laser scanning microscope comprising (a) means for producing a scanning beam of ultrashort laser light pulses, said

scanning beam producing means comprising (i) a laser source for providing a beam of ultrashort laser light pulses comprising photons of a second characteristic energy, wherein said second characteristic energy is less than said first characteristic energy and wherein the simultaneous absorption of a plurality of said photons of said second characteristic energy by said fluorescent molecules causes the fluorescence of said fluorescent molecules, (ii) a first acousto-optical deflector optically coupled to said laser source for scanning said beam along a first axis, (iii) a first spectrally dispersive element optically coupled to said first acousto-optical deflector, said first spectrally dispersive element being oriented relative to said first acousto-optical deflector so as to disperse multi-chromatic light in a direction opposite to that dispersed by said first acousto-optical deflector; (b) means for focusing said scanning beam to a focal point within said sample to produce an illumination intensity sufficiently high only at said focal point to produce molecular excitation and fluorescence of said sample by simultaneous absorption of at least two incident photons; (c) means for detecting the fluorescence produced by said sample; and (d) means for using the detected fluorescence to form a magnified image of the sample.

Preferably, the first spectrally dispersive element of the aforementioned microscope is constructed to disperse multi-chromatic light, for at least a portion of said multi-chromatic light, in an amount equal to that dispersed by said first acousto-optical deflector. The scanning beam producing means of the microscope described above preferably further comprises means for scanning the sample in a direction perpendicular to said first axis, said means for scanning the sample in a direction perpendicular to said first axis comprising a scanning mirror or a second acousto-optical deflector and a second spectrally dispersive element, said second spectrally dispersive element being

oriented relative to said second acousto-optical deflector so as to disperse multi-chromatic light in a direction opposite to that dispersed by said second acousto-optical deflector.

The present invention is still further directed to a laser scanning microscope for forming a magnified image of a sample, the sample containing fluorophores, said laser scanning microscope comprising (a) means for producing a scanning beam of light pulses, said scanning beam producing means comprising (i) means for providing a beam of light pulses, said light pulses being of a wavelength suitable to excite said fluorophores, (ii) a first acousto-optical deflector optically coupled to said beam providing means for scanning said beam along a first axis, (iii) a first spectrally dispersive element optically coupled to said first acousto-optical deflector, said first spectrally dispersive element being oriented relative to said first acousto-optical deflector so as to disperse multi-chromatic light in a direction opposite to that dispersed by said first acousto-optical deflector; (b) means for focusing said scanning beam at a focal point within said sample; (c) means for detecting the fluorescence produced by said sample; and (d) means for using the detected fluorescence to form a magnified image of the sample.

The present invention is yet further directed to a method of imaging a sample using multi-harmonic generation laser scanning microscopy, said method comprising the steps of (a) providing a sample, the sample containing molecules having the appropriate nonlinear susceptibility; (b) producing a scanning beam of ultrashort laser light pulses, said scanning beam being produced by (i) providing a beam of ultrashort light pulses comprising photons of a first wavelength capable of interacting with said molecules having the appropriate nonlinear susceptibility to create, by multi-harmonic generation, photons of a second wavelength, (ii) passing said beam through a spectrally dispersive element, and (iii) deflecting said beam using an acousto-optical deflector, (iv) wherein

said spectrally dispersive element is oriented to disperse multi-chromatic light in a direction opposite to that dispersed by said acousto-optical deflector; (c) focusing said scanning beam at a focal point within said sample to produce an illumination intensity sufficiently high only at said focal point to generate, by multi-harmonic generation, photons of said second wavelength; (d) detecting the photons of said second wavelength emitted from said sample; and (e) using the detected photons of said second wavelength to form an image of the sample.

Preferably, the spectrally dispersive element used in the aforementioned method is constructed to disperse multi-chromatic light, for at least a portion of said multi-chromatic light, in an amount equal to that dispersed by said acousto-optical deflector. The scanning beam producing step described above preferably further comprises scanning the sample in a direction perpendicular to said first axis, said scanning in a direction perpendicular to said first axis comprising the use of a scanning mirror or a second acousto-optical deflector and a second spectrally dispersive element, said second spectrally dispersive element being oriented relative to said second acousto-optical deflector so as to disperse multi-chromatic light in a direction opposite to that dispersed by said second acousto-optical deflector.

The present invention is further directed to a multi-harmonic generation laser scanning microscope for forming a magnified image of a sample, the sample containing molecules having the appropriate nonlinear susceptibility, said multi-harmonic generation laser scanning microscope comprising (a) means for producing a scanning beam of ultrashort laser light pulses, said scanning beam producing means comprising (i) a laser source for providing a beam of ultrashort light pulses comprising photons of a first wavelength capable of interacting with said molecules having the appropriate nonlinear susceptibility to create, by multi-harmonic generation, photons of a second

wavelength, (ii) a first acousto-optical deflector optically coupled to said laser source for scanning said beam along a first axis, (iii) a first spectrally dispersive element optically coupled to said first acousto-optical deflector, said first spectrally dispersive element being oriented relative to said first acousto-optical deflector so as to disperse multi-chromatic light in a direction opposite to that dispersed by said first acousto-optical deflector; (b) means for focusing said scanning beam at a focal point within said sample to produce an illumination intensity sufficiently high only at said focal point to generate, by multi-harmonic generation, photons of said second wavelength; (c) means for detecting the photons of said second wavelength emitted from said sample; and (d) means for using the detected photons of said second wavelength to form an image of the sample.

Preferably, the first spectrally dispersive element of the aforementioned microscope is constructed to disperse multi-chromatic light, for at least a portion of said multi-chromatic light, in an amount equal to that dispersed by said first acousto-optical deflector. The scanning beam producing means of the microscope described above preferably further comprises means for scanning the sample in a direction perpendicular to said first axis, said means for scanning the sample in a direction perpendicular to said first axis comprising a scanning mirror or a second acousto-optical deflector and a second spectrally dispersive element, said second spectrally dispersive element being oriented relative to said second acousto-optical deflector so as to disperse multi-chromatic light in a direction opposite to that dispersed by said second acousto-optical deflector.

Additional objects, features, aspects and advantages of the present invention will be set forth, in part, in the description which follows and, in part, will be obvious from the description or may be learned by practice of the invention. In the description, reference is made to the accompanying drawings which form a part thereof and in which are shown by way of illustration specific





## **BRIEF DESCRIPTION OF THE DRAWINGS**

The accompanying drawings, which are hereby incorporated into and constitute a part of this specification, illustrate preferred embodiments of the invention and, together with the description, serve to explain the principles of the invention. In the drawings wherein like reference numerals represent like parts:

Fig. 1A is a schematic diagram illustrating the problem of unwanted spectral dispersion of a multi-chromatic ultrashort light pulse by a conventional acousto-optical deflector;

Fig. 1B is a schematic diagram illustrating how a prism may be used in accordance with the teachings of the present invention to compensate for the unwanted spectral dispersion of a multi-chromatic ultrashort light pulse caused by a conventional acousto-optical deflector;

Fig. 2 is a schematic diagram of a first embodiment of an apparatus adapted for compensating for the spectral dispersion of multi-chromatic light by an acousto-optical deflector, said apparatus being constructed according to the teachings of the present invention;

Fig. 3 is a partially exploded perspective view of an implementation of the apparatus of Fig. 2;

Fig. 4 is a schematic diagram of a first embodiment of an apparatus for steering a beam of light, said apparatus being constructed according to the teachings of the present invention;

Figs. 5A and 5B are two-photon laser scanning microscopic images of a 2.5 $\mu$ m spherical object using 100 fs pulses at 900 nm, without and with, respectively, the addition of the dispersion-compensating apparatus of Fig. 2;

Fig. 6 is a schematic diagram of a second embodiment of an apparatus for compensating for the spectral dispersion of multi-chromatic light by an acousto-optical deflector, said apparatus being constructed according to the teachings of the present invention;

Fig. 7 is a schematic diagram of a second embodiment of an apparatus for steering a beam of light, said apparatus being constructed according to the teachings of the present invention;

Fig. 8 is a schematic diagram of a third embodiment of an apparatus for steering a beam of light, said apparatus being constructed according to the teachings of the present invention;

Fig. 9A is a schematic diagram illustrating the phenomenon of group velocity dispersion in the context of an ultrashort light pulse transmitted through scanning optics;

Fig. 9B is a schematic diagram illustrating an apparatus for compensating for the group velocity dispersion shown in Fig. 9A;

Fig. 10 is a schematic diagram illustrating a fourth embodiment of an apparatus for steering a beam of light, said apparatus being constructed according to the teachings of the present invention;

Fig. 11 is a schematic diagram of one embodiment of a laser scanning microscope constructed according to the teachings of the present invention, said laser scanning microscope being capable of operating in a single-photon confocal mode, a multi-photon excited fluorescence mode and a multi-harmonic generation mode;

Figs. 12A through 12D are images of fluorescent pollen grains obtained using the laser scanning microscope of Fig. 11 in a two-photon excited fluorescence mode, using 100 fs pulses centered at 900 nm for illumination and image acquisition rates of (A) 30 Hz; (B) 120 Hz; (C) 240 Hz; and (D) 480 Hz, respectively (scale bar = 20  $\mu\text{m}$ );

Figs. 13A and 13B are images of a pair of fluorescent pollen grains obtained using the laser scanning microscope of Fig. 11 in a two-photon excited fluorescence mode, using 1.5 ps pulses centered at 900 nm for illumination and an image acquisition rate of 30 Hz (scale bar = 5  $\mu$ m);

Fig. 14 is a series of sectional images (each image averaged over 32 scans, adjacent images representing sections spaced 2  $\mu$ m apart in the vertical axis) of a fluorescent pollen grain obtained using the laser scanning microscope of Fig. 11 in a two-photon excited fluorescence mode, using 1.5 ps pulses centered at 900 nm for illumination and an image acquisition rate of 30 Hz (scale bar = 20  $\mu$ m);

Fig. 15 is an image of neurons expressing green fluorescent protein from the Dor 47A promoter in the brain of a living fruit fly, *Drosophila melanogaster*, obtained using the laser scanning microscope of Fig. 11 in a two-photon excited fluorescence mode, using 100 fs pulses at 900 nm for illumination at an image acquisition rate of 30 Hz (scale bar = 10  $\mu$ m);

Figs. 16(a) and 16(b) are images of a CHO cell stained with 10  $\mu$ M DiA obtained using the laser scanning microscope of Fig. 11 in a two-photon excited fluorescence mode and in a multi-harmonic generation mode, respectively, using 100 fs pulses at 900 nm for illumination;

Figs. 17(a) and 17(b) are images of hippocampal neurons stained with 10  $\mu$ M FM1-43 obtained using the laser scanning microscope of Fig. 11 in a two-photon excited fluorescence mode and in a multi-harmonic generation mode, respectively, using 100 fs pulses at 900 nm for illumination;

Fig. 18 is a single frame in a series of 300 images, acquired at 30 Hz, of a hippocampal neuron stained with 5  $\mu$ M Fluo-3 AM ester for 30 minutes, the images being obtained using the laser

scanning microscope of Fig. 11 in a two-photon excited fluorescence mode using 100 fs pulses at 900 nm for illumination;

Fig. 19 is an image identifying three regions of interest within the neuron of Fig. 18: (1) the nucleus, (2) the cytoplasm and (3) a dendrite; and

Fig. 20 is a graph showing the average fluorescence intensity in each of the three regions of the neuron of Fig. 18 during electric field stimulation consisting of five 500 ms trains, each such train containing twelve 2 ms pulses of 30 V/cm.

Figure 19: A fluorescence image of a neuron with three regions of interest (ROIs) identified: (1) the nucleus, (2) the cytoplasm, and (3) a dendrite. The ROIs are marked with small squares and labeled with numbers 1, 2, and 3.

## **DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS**

As noted above, the present invention is based, in large part, on the inventors' unexpected discovery that the spectral dispersion of multi-chromatic ultrashort light pulses by an acousto-optical deflector can be significantly ameliorated by positioning a dispersive element, such as a prism, along the path of the multi-chromatic ultrashort light pulses in such a way that said dispersive element disperses the multi-chromatic ultrashort light pulses in a direction opposite to the spectral dispersion caused by the acousto-optical deflector. As will be seen below, the aforementioned dispersive element may be positioned either before or after the acousto-optical deflector.

The aforementioned principle is aptly illustrated by reference to Figs. 1A and 1B. As seen in Fig. 1A, when a beam of ultrashort light pulses having a center wavelength of 900 nm and a bandwidth of 20 nm arrives at a conventional acousto-optical deflector 11, a portion of the beam travels undeflected through deflector 11 and another portion of the beam is deflected by deflector 11 at approximately twice the Bragg angle. (Since multi-chromatic light is being used, the Bragg angle referred to herein is to the Bragg angle for the center wavelength of the multi-chromatic light.) The longer wavelengths within the beam are deflected slightly more than twice the Bragg angle, the shorter wavelengths within the beam are deflected slightly less than twice the Bragg angle, and the center wavelength within the beam is deflected at twice the Bragg angle. For the reasons discussed above, such spectral dispersion of the deflected beam is clearly undesirable in many instances.

Referring now to Fig. 1B, it can be seen that by positioning a prism 13 along the path of the incident beam of ultrashort light pulses so that prism 13 disperses the incident beam in a direction opposite to the direction of dispersion subsequently caused by deflector 11 and by an amount equal thereto, one can offset, to a substantial extent, the dispersion caused by deflector 11 and can

collimate the deflected light. Due to the slight variation of the normalized dispersion across the scan area, the dispersion is fully corrected only at the center frequency of the scan; nevertheless, the overall dispersion can be greatly reduced throughout and is at least 80-90% corrected even at the extremes of the scan area.

As can readily be appreciated, the amount of unwanted dispersion introduced into the deflected beam by the acousto-optical deflector is preferably matched by the amount of oppositely-directed dispersion provided by the prism or other dispersive element. Therefore, to assist one in selecting an appropriate prism, the following relationship governing the deflection of a beam of light by a prism is provided:

$$\delta = 2 \cdot \sin^{-1}[n(\lambda) \cdot \sin(\frac{\phi}{2})] - \phi \quad [\text{Eq. 2}]$$

where  $\delta$  = the deflection of the beam,  $n(\lambda)$  = the index of refraction of the prism material at wavelength  $\lambda$ , and  $\phi$  = the apex angle of the prism. From this, the normalized dispersion is represented as follows:

$$\text{normalized dispersion} \equiv \frac{\delta(\lambda - \Delta\lambda) + \delta(\lambda + \Delta\lambda)}{2\Delta\lambda} \quad [\text{Eq. 3}]$$

Different types of prism materials have different dispersive properties determined by their refractive index,  $n(\lambda)$ . Table II, generated using Equations 2 and 3, tabulates the dispersion of a light pulse with a center wavelength of 900 nm and a bandwidth of 20 nm by a prism made of SF10 glass (Schott Glass Technologies) as a function of its apex angle. For such a light pulse, it can be seen that a prism with an apex angle of 58.4 degrees matches the dispersion of 0.00365 deg/nm caused by an acousto-optical deflector operating at 275 MHz and having an acoustic velocity of 4322 m/s.

TABLE II

Prism Apex Angle (deg)	Deflection at 890 nm n=1.707374 (deg)	Deflection at 910 nm n=1.706651 (deg)	Deflection at 900 nm n=1.707007 (deg)	Deflection Difference 890-910 nm (deg/20nm)	Normalized Dispersion at 900 nm (deg/nm)
40	31.46	31.42	31.44	-0.0349	-0.0017451
41	32.44	32.41	32.43	-0.0362	-0.0018097
42	33.45	33.41	33.43	-0.0375	-0.0018766
43	34.48	34.44	34.46	-0.0389	-0.0019461
44	35.52	35.48	35.50	-0.0404	-0.0020184
45	36.59	36.55	36.57	-0.0419	-0.0020937
46	37.69	37.65	37.67	-0.0434	-0.0021724
47	38.81	38.77	38.79	-0.0451	-0.0022548
48	39.97	39.92	39.94	-0.0468	-0.0023412
49	41.15	41.10	41.13	-0.0486	-0.0024321
50	42.37	42.32	42.34	-0.0506	-0.0025281
51	43.62	43.57	43.60	-0.0526	-0.0026296
52	44.91	44.86	44.89	-0.0548	-0.0027375
53	46.25	46.19	46.22	-0.0571	-0.0028525
54	47.63	47.57	47.60	-0.0595	-0.0029757
55	49.07	49.01	49.04	-0.0622	-0.0031082
56	50.56	50.49	50.53	-0.0650	-0.0032514
57	52.11	52.04	52.08	-0.0681	-0.0034071
58	53.74	53.67	53.70	-0.0716	-0.0035776
59	55.44	55.36	55.40	-0.0753	-0.0037657



60	57.23	57.15	57.19	-0.0795	-0.0039749
61	59.12	59.04	59.08	-0.0842	-0.0042100
62	61.13	61.04	61.09	-0.0896	-0.0044776
63	63.28	63.18	63.23	-0.0957	-0.0047864
58.4	54.41	54.33	54.37	-0.0730	-0.0036506

Referring now to Figs. 2 and 3, there are shown schematic and partially exploded perspective views, respectively, of a first embodiment of an apparatus adapted for compensating for the spectral dispersion of multi-chromatic light by an acousto-optical deflector, said apparatus being constructed according to the teachings of the present invention and being represented generally by reference numeral 31.

Apparatus 31, which is particularly well-suited for placement along a beam path in front of an acousto-optical deflector, comprises a prism 13 and a pair of planar mirrors 33 and 35. Mirrors 33 and 35 are positioned after prism 13 and are used to restore the prism-dispersed beam to its original path. (If restoration of the dispersed beam to its original path is not necessary, mirrors 33 and 35 may be omitted.) Mirror 33 is fixedly mounted on a lever arm 37, lever arm 37 being rotatably mounted on a shaft 39 disposed within a bearing 40 (bearing 40 shown in Fig. 3 only). A linear motor 41 and a return spring 43 are mechanically coupled to lever arm 37 (above the plane of the input beam) and are used to rotate arm 37 and mirror 33 about shaft 39. Mirror 35 is kept stationary. The rotational adjustability of mirror 33 enables apparatus 31 to function over a broad spectral range by compensating for the wavelength-dependent variation in the deflection of the beam by prism 13 in such a way as to enable the center wavelength of the dispersed beam to be restored to its original path. To illustrate the wavelength-dependent variation in the deflection of the center

wavelength by a prism, TABLE III lists several wavelengths commonly used in laser-scanning microscopy, the indices of refraction of SF10 glass at these wavelengths, and the deflection angles produced at these wavelengths by an SF10 glass prism with an apex angle of 58.4 degrees.

TABLE III

Wavelength (nm)	Index of Refraction	Deflection Angle (deg.)
456	1.75497	59.38
488	1.74602	58.42
514	1.74019	57.80
543	1.73481	57.23
633	1.72307	56.01
800	1.71124	54.80
850	1.70895	54.57
900	1.70701	54.37

Preferably, the rotation of mirror 33 by motor 41 is placed under software control so that exact beam alignment is performed automatically for each selected wavelength.

As seen in Fig. 3, apparatus 31 further comprises a base plate 45, upon which the foregoing components of apparatus 31 are directly or indirectly mounted.

As can readily be appreciated, prism 13 must be positioned to lie in the plane of the scan that will thereafter be performed by the acousto-optical deflector (or in its optically equivalent plane if there are intermediate mirrors). Such an arrangement ensures that the dispersion introduced by prism 13 is in a direction opposite to that introduced by the acousto-optical deflector. Light passing through prism 13 must be collimated within said plane (hence lens 47 shown in Fig. 3) but may be slightly convergent or divergent in the perpendicular direction. These requirements are similar to

the input requirements for an acousto-optical deflector. Preferably, the beam should be P-polarized with respect to its intersection with the prism surface and should enter and leave the prism at or near the Brewster angle (with respect to the surface normal) calculated for the designated wavelength and prism glass. Under these conditions, reflections from the prism surfaces are minimized and the best efficiency is achieved. The prism is preferably provided with antireflective coatings that are selected for these incidence angles and the relevant wavelengths.

Referring now to Fig. 4, there is shown a schematic diagram of a first embodiment of an apparatus for steering a beam of light, said apparatus being constructed according to the teachings of the present invention and being represented generally by reference numeral 71.

Apparatus 71 comprises a combination of apparatus 31 and acousto-optical deflector 11. Deflector 11 is positioned along the path of the beam outputted by apparatus 31, and apparatus and deflector 11 are oriented relative to one another so that apparatus 31 compensates for the spectral dispersion of multi-chromatic light subsequently caused by deflector 11. A mirror 73 is positioned between apparatus 31 and deflector 11 to direct the outputted beam from apparatus 31 to deflector 11, and mirror 73 and deflector 11 are rotatable as a unit to keep the exit beam aligned to the optic axis for any Bragg angle.

Apparatus 71 is most compatible with light in the visible to infrared range (i.e., about 400 to 1000 nm) wherein the bandwidth is less than or equal to about 40 nm. The aforementioned upper wavelength limit stems from the fact that, at said upper wavelengths, the corrective prism is unable to introduce sufficient dispersion to fully offset that introduced by the acousto-optical deflector. The lower wavelength limit is attributable to the reduced transmission of many optical components at said short wavelengths.

Apparatus 71 is suitable for use in a variety of applications that involve beam scanning, such as in a multi-harmonic generation laser scanning microscope, a single-photon excited fluorescence laser scanning microscope and a multi-photon excited fluorescence laser scanning microscope (e.g., for analyzing or perturbing fast physiological processes in cultured cells and tissues, in explanted tissues, in exposed tissues and in intact organisms). When apparatus 71 is used in multi-harmonic generation laser scanning microscopy or in multi-photon excited fluorescence laser scanning microscopy, light pulses in either the picosecond or femtosecond regimes may be used. Although picosecond pulses are essentially monochromatic (bandwidth  $\leq 1$  nm) and, thus, suffer less lateral dispersion by the acousto-optical deflector than do femtosecond pulses, femtosecond pulses are preferred due to their higher peak power and, thus, higher two-photon excitation efficiency and multi-harmonic generation efficiency. As can readily be appreciated, apparatus 71 could be used in a laser scanning microscope that has both single-photon confocal and multi-photon non-confocal modes, as well as a multi-harmonic generation mode.

The benefits of using the dispersion-correcting optics of the present invention in multi-photon laser scanning microscopy can readily be seen by a comparison of Fig. 5A to Fig. 5B. In Fig. 5A, there is shown a two-photon image of a 2.5  $\mu\text{m}$  spherical InSpeck Bead (Molecular Probes) obtained using 100 fs pulses at 900 nm. In Fig. 5B, the same object is imaged under the same conditions, except that the dispersion-compensating optics of the present invention are additionally employed. As can be seen, the resolution and signal-to-noise ratio are appreciably improved with the addition of the dispersion-compensating optics of the present invention.

Apparatus 71 is also well-suited for many other applications in which light beams must be steered rapidly or in patterns that do not conform to linear or sinusoidal scans, such as in

photochemistry *in vitro* and *in vivo* (e.g., to activate photosensitive molecules capable of effecting changes in cellular microenvironments), in materials processing (e.g., etching, pattern reproduction), in cell or tissue ablation, and in optical memory devices.

As noted above, the present invention achieves complete dispersion correction at only one scan position, typically chosen to lie in the center of the scan area. To achieve complete dispersion correction across the entire scan area, optics whose magnification is proportional to wavelength would have to be placed after the acousto-optical deflector. Thus, the angular deflection of longer wavelengths would be proportionally decreased and that of shorter wavelengths would be proportionally increased. A further requirement would be that the system remain par-focal for the entire pulse bandwidth (i.e., beam collimation is not wavelength dependent).

Referring now to Fig. 6, there is shown a schematic diagram of a second embodiment of an apparatus for compensating for the spectral dispersion of multi-chromatic light by an acousto-optical deflector, said apparatus being constructed according to the teachings of the present invention and being represented generally by reference numeral 91.

Apparatus 91 is similar in many respects to apparatus 31, the principal difference between the two apparatuses being that the positions of prism 13 and fixed mirror 35 are reversed in apparatus 91, as compared to apparatus 31.

Referring now to Fig. 7, there is shown a schematic diagram of a second embodiment of an apparatus for steering a beam of light, said apparatus being constructed according to the teachings of the present invention and being represented generally by reference numeral 101.

Apparatus 101 is similar to apparatus 71, apparatus 101 comprising a combination of acousto-optical deflector 11 and a mirror image apparatus 31' of apparatus 31. Apparatus 31' and

deflector 11 are oriented relative to one another so that apparatus 31' compensates for the spectral dispersion of multi-chromatic light previously caused by deflector 11. A mirror 103 is positioned in front of deflector 11 to direct an input beam to deflector 11, and mirror 103 and deflector 11 are rotatable as a unit to keep the exit beam aligned to the optic axis for any Bragg angle.

In general, it is preferable to position the dispersion-compensating apparatus before the acousto-optical deflector, as in apparatus 71, instead of after the acousto-optical deflector, as in apparatus 101. This is because the former arrangement places the dispersion-compensating optics at a location where the exciting beam is stationary and collimated in the scan direction. Such an arrangement also ensures that the alignment of the corrective optics is independent of any other adjustments that may be needed, such as matching the Bragg conditions of the acousto-optical deflector, collimation adjustments, astigmatism, etc. Placing the acousto-optical deflector before the dispersion-compensating apparatus also requires that the beam deflections by the acousto-optical deflector be small.

A schematic diagram of a third embodiment of a beam-steering apparatus is shown in Fig. 8 and is represented generally by reference numeral 131. As can be seen, apparatus 131 comprises prism 13, acousto-optical deflector 11 positioned after prism 13, a first mirror 133 positioned between prism 13 and deflector 11 and rotatable about a shaft 134, and a second mirror 135 positioned after deflector 11 and rotatable about a shaft 136. Preferably, rotation of rotatable mirrors 133 and 135 is controlled by computer. In this arrangement, the rotational adjustment for aligning the center wavelength of the beam exiting the prism, and the rotational adjustment for matching the Bragg angle conditions at the acousto-optical deflector are combined, and the deflector remains stationary.

The propagation of broad-band pulses through dispersive media, such as those found in the various beam-steering apparatuses described above, typically results in the shorter wavelength components of the pulses being delayed relative to the longer wavelength components of the pulses and, hence, in the temporal spreading of the pulses (see Fig. 9A). This pulse-spreading phenomenon is typically referred to in the art as group velocity dispersion and is clearly undesirable for many applications, such as multi-photon laser scanning microscopy, wherein short pulse lengths and high peak powers are necessary. Consequently, it may be desirable to precede the beam-steering apparatuses of the present invention with an apparatus for temporally advancing the shorter wavelength components relative to the longer wavelength components and thereby compensating for group velocity dispersion. An illustrative group velocity dispersion compensation apparatus is schematically shown in Fig. 9B and is represented by reference numeral 151. Apparatus 151 comprises a mirror 153, a pair of prisms 155 and 157, and a mirror 159. In use, a light pulse travels past mirror 153, is transmitted through prisms 155 and 157, is reflected off mirror 159, is transmitted back through prisms 157 and 155, and is reflected off mirror 153.

The beam-steering apparatuses described above may be used in multi-photon laser scanning microscopy, in multi-harmonic generation laser scanning microscopy and in other applications to scan in the “fast” or x-axis. In such applications, a conventional galvanometric mirror or the like may also be used to scan in the “slow” or y-axis. At 30 Hz (video rate), such a beam typically sweeps an area of 512 pixels in the fast axis and 480 pixels in the slow axis. In this type of “single acousto-optical deflector” arrangement, higher scan rates (up to or exceeding 480 Hz) are possible by reducing the scan area such that the beam visits each pixel more frequently.

An alternative arrangement, shown in Fig. 10, uses acousto-optical deflectors and dispersion-compensating optics to scan in both the x- and y-axes. Even if efficient excitation requires a minimum dwell time of the exciting beam on each pixel (such that acquisition of full-sized images at, for example, 480 Hz would lead to a prohibitively low signal-to-noise ratio), such a “dual acousto-optical deflector” arrangement would have utility in the following two areas: (1) in flexible imaging area selection at high scan rates; and (2) in random access. With respect to the former, as can be appreciated, imaging areas with a “single acousto-optical deflector” is constrained by the inert mass of the galvanometric mirror scanning the slow axis. At high scan speeds, the amplitude of mirror excursions has to be kept small, with a consequent reduction of the scan range in the y-axis. This constrains the aspect ratio of the scanned area to an oblong rectangular format (see Figs. 12A through 12D wherein the use of a scan mirror in the slow axis constrains the aspect ratio of the images in Figs. 12C and 12D obtained at high image acquisition frequencies). A “dual acousto-optical deflector” arrangement is not subject to this limitation.

The “dual acousto-optical deflector” arrangement described above is not only capable of producing fast linear scans in both the x and y axes, it also allows the exciting light beam to move virtually instantaneously from any given pixel to any other pixel within the imaging area. The exciting light beam can, therefore, visit any predefined set of pixels (which need not be contiguous) in any temporal sequence and at very short intervals, the deflectors effectively shuttering the beam while in transit. As can readily be appreciated, there are many applications where it would be desirable to interrogate defined areas of interest at very high (i.e., kHz) repetition rates, rather than to acquire full-sized images (which will contain much useless information) at much lower rates. Random access achieves this objective.



Referring now to Fig. 11, there is shown a schematic diagram of one embodiment of a laser scanning microscope constructed according to the teachings of the present invention, said laser scanning microscope being represented generally by reference numeral 201.

Microscope 201, which is capable of operating in one or more of a single-photon fluorescence confocal mode, a multi-photon excited fluorescence mode and a multi-harmonic generation mode, comprises two alternative illumination sources, namely, a pulsed infrared laser 203 and a continuous visible laser 205. The output of pulsed infrared laser 203 is optically coupled to group velocity dispersion compensation apparatus 151 whose output, in turn, is coupled to beam-shaping optics 207. The output from beam-shaping optics 207 is then reflected off a beam splitter 208, where it is inputted into dispersion compensation optics 209 comprising prism 13, mirror 33 and mirror 35. (Laser 205 is oriented so that its output is passed through beam splitter 208 to dispersion compensation optics 209.) The output from dispersion compensation optics 209 is then inputted into acousto-optical deflector 11, which scans the beam along one axis.

The scanning beam is then reflected off a selectable beam-splitter 211 onto a scanning mirror 213, which scans the beam along a second axis. The thus twice-scanned beam is then passed through a selectable beam splitter 215 and then brought to focus on a specimen using an objective 217. Light emitted from the specimen in the forward direction is collected by a matching objective 219, reflected off a long-pass beam-splitter 221 and then detected using multi-harmonic detection optics 223. Light emitted from the specimen in a backward direction is passed back through objective 217 and is then split by selectable beam-splitter 215 into a first component that is then detected by non-confocal fluorescence detection optics 225 and a second component that travels back across scanning mirror 213 and through beam-splitter 211 to confocal fluorescence detection optics 227.

The detection signals from multi-harmonic detection optics 223, non-confocal fluorescence detection optics 225 and confocal fluorescence detection optics 227 are then inputted to a computer 231, which uses the detection signals to form an image of the specimen, said image then being displayed on a display 233.

Referring now to Figs. 12A through 12D, there are shown images of fluorescent pollen grains obtained using laser scanning microscope 201 in a two-photon excited fluorescence mode with 100 fs pulses centered at 900 nm being used for illumination and image acquisition rates of (A) 30 Hz; (B) 120 Hz; (C) 240 Hz; and (D) 480 Hz, respectively (scale bar = 20  $\mu\text{m}$ ).

Referring now to Figs. 13A and 13B, there are shown images of a pair of fluorescent pollen grains obtained using laser scanning microscope 201 in a two-photon excited fluorescence mode with 1.5 ps pulses centered at 900 nm for illumination and an image acquisition rate of 30 Hz (scale bar = 5  $\mu\text{m}$ ).

Referring now to Fig. 14, there is shown a series of sectional images (each image averaged over 32 scans, adjacent images representing sections spaced 2  $\mu\text{m}$  apart in the vertical axis) of a fluorescent pollen grain obtained using laser scanning microscope 201 in a two-photon excited fluorescence mode with 1.5 ps pulses centered at 900 nm for illumination and an image acquisition rate of 30 Hz (scale bar = 20  $\mu\text{m}$ ).

Referring now to Fig. 15, there is shown an image of neurons expressing green fluorescent protein from the Dor 47A promoter in the brain of a living fruit fly, *Drosophila melanogaster*, said image obtained using laser scanning microscope 201 in a two-photon excited fluorescence mode with 100 fs pulses at 900 nm for illumination at an image acquisition rate of 30 Hz (scale bar = 10  $\mu\text{m}$ ).

Referring now to Figs. 16(a) and 16(b), there are shown images of a CHO cell stained with 10  $\mu$ M 4-(4-(dihexadecylamino)styryl)-N-methylpyridinium iodide (commercially available as DiA dye, Molecular Probes, Eugene, OR), said images being obtained using laser scanning microscope 201 in a two-photon excited fluorescence mode and in a multi-harmonic generation mode, respectively, with 100 fs pulses at 900 nm being used for illumination.

Referring now to Figs. 17(a) and 17(b), there are shown images of hippocampal neurons stained with 10  $\mu$ M N-(3-triethylammoniumpropyl)-4-(4-(dibutylamino)styryl)pyridinium dibromide (commercially available as FM<sup>®</sup> 1-43 dye, Molecular Probes, Eugene, OR), said images being obtained using laser scanning microscope 201 in a two-photon excited fluorescence mode and in a multi-harmonic generation mode, respectively, with 100 fs pulses at 900 nm being used for illumination.

Referring now to Fig. 18, there is shown a single frame in a series of 300 images, acquired at 30 Hz, of a hippocampal neuron stained with 5  $\mu$ M glycine, N-[4-[6-[(acetyloxy)methoxy]-2,7-dichloro-3-oxo-3H-xanthen-9-yl]-2-[2-[2-[bis[2-[(acetyloxy)methoxy]-2-oxyethyl]amino]-5-methylphenoxy]ethoxy]phenyl]-N-[2-[(acetyloxy)methoxy]-2-oxyethyl]-, (acetyloxy)methyl ester (commercially available as Molecular Probes, Eugene, OR) for 30 minutes, the images being obtained using laser scanning microscope 201 in a two-photon excited fluorescence mode, with 100 fs pulses at 900 nm being used for illumination.

Referring now to Fig. 19, there is shown an image identifying three regions of interest within the neuron of Fig. 18: (1) the nucleus, (2) the cytoplasm and (3) a dendrite. Fig. 20 is a graph showing the average fluorescence intensity in each of the three regions of the neuron of Fig. 18

during electric field stimulation consisting of five 500 ms trains, each such train containing twelve 2 ms pulses of 30 V/cm.

The embodiments of the present invention recited herein are intended to be merely exemplary and those skilled in the art will be able to make numerous variations and modifications to it without departing from the spirit of the present invention. All such variations and modifications are intended to be within the scope of the present invention as defined by the claims appended hereto.

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206  
2207  
2208  
2209  
2210  
2211  
2212  
2213  
2214  
2215  
2216  
2217  
2218  
2219  
2220  
2221  
2222  
2223  
2